

Pokini

Small. Powerful. Flexible.




Available until 2026

Casted aluminum case

For 24x7 use

Optional WLAN//4xLAN



fanless



certified dust protection



temperature range: -40°F up to 158°F



optional VESA/DIN-Rail mount

OS	Microsoft Windows 7 / 8.1 Professional Microsoft Windows 10 Professional / IoT Linux (Suse / Ubuntu / Redhat)
CPU	AMD® A10 Micro-6700T (4x 1,20 GHz up to 2,20 GHz)
RAM	1x SO-DIMM DDR3 PC1333, max. 8 GB
Storage	1x mSATA
Graphics	AMD® Radeon R6
Display Interface 1	HDMI 1.4a (1920 x 1200 @ 60Hz)
Display Interface 2	HDMI 1.4a (1920 x 1200 @ 60Hz)
Audio	Realtek ALC886 - 7.1 HD Audio
LAN	1x RJ45 @ 10/100/1000 Mbit/s (Intel® I211)
Rear interfaces	1x USB 3.0 1x USB 2.0 2x HDMI 1x LAN 1x mini-serial RS232 (with DB9 adaptor) 1x 8-Bit GPIO DC-In
Front interfaces	1x USB 3.0 2x USB 2.0 Line-Out, Line-In microSD-Card slot Power-Button
Internal interfaces	1x microSIM (6 Pins)

Available extension-kits:

Pokini F C67 Entry	Without any extenctions
Pokini F C67 WLAN	WLAN 802.11ac (2.4/5GHz Intel 7260HMW) Bluetooth 4.0 1x eSATA (powered) 1x additional GbE LAN (dedicated Intel® I211)
Pokini F C67 4LAN	3x additional GbE LAN (dedicated Intel® I211)
Special features	Auto-Power-On, Wake-on-LAN, Wake-on-Timer, PXE-Boot, Watchdog
Power supply	Power-input: 10-15W Consumption: 4,5W - 10,5W
Measurements	108mm x 24mm x 83mm, approx. 400g
Warranty	5 years bring-in warranty